



PHOTOMETRIC STANDARD COMPLIANCE



ICAO ANNEX 14, VOLUME I  
TYPE A - LOW INTENSITY OBSTACLE LIGHT

CAA- CAP 168 – LOW INTENSITY GROUP A

KEY FEATURES

- designed and manufactured in Italy by Clampco Sistemi
- patented technology
- easy way for mounting – plug 'n' play connection
- the lowest weight and power consumption in the market
- extended power supply range: 10 to 60 Vdc, 110-230Vac
- horizontal and vertical fixings

SPECIFICATIONS

	LIOLA-P1_22S	LIOLA-P1_23S
Order Code		
Typical use		Night time
Light source		LED
Type of beacon		Steady
Colour		Red according to CIE Chromaticity Boundary
Light Intensity		>10 cd
Horizontal coverage		360°
Input voltage	10 ÷ 60 Vdc	110 ÷ 230 Vac
Power consumption	1.6 W	2 W
Average life		100 000 hours
Temperature range	-40 to +55 °C	-30 °C to +55 °C
Protection degree		IP66
Material of the body		Glass Reinforced Plastic red body (UL94-HB)
Material of the transparent cap		Polycarbonate (UL94-V2)
Connection		M/F connector IP66/68 for cable up to ø 7 - 13 mm
Weight		700 g
Fixing		Stainless steel anchor basement for poles with diameter up to 82 mm.
Optional fixing SCSG_HDGS		Mounting hardware for "L" shaped sections (50x50 mm min.; 160x160 mm max.); circular profiles (min. ø = 48,3 mm; max. ø 219,1 mm). Adjustable fixing plate (± 60° on the horizontal plan)

TECHNICAL DRAWINGS

