



PHOTOMETRIC STANDARD COMPLIANCE



ICAO ANNEX 14, VOLUME I
TYPE A & C - MEDIUM INTENSITY OBSTACLE LIGHT



FAA AC 150/5345-43F;
TYPE L-865

KEY FEATURES

- designed and manufactured in Italy by Clampco Sistemi
- fully compliant with former SEGS23P20K_C2K_15 model
- easy way for mounting – plug 'n' play connection
- EMF immunity up to 60V/m

SPECIFICATIONS

Order Code	MIOLAC-M1_23S
Lamp ID	SEGS23P20K_C2K_15
Typical use	day and night time
Light source	LED
Type of beacon	Flashing (day mode) and Steady (night mode)
Colour	white day mode / red night mode according to CIE Chromaticity Boundary
Light Intensity	20.000 cd day mode / 2.000 cd night mode
Flashing rate	20 ± 40 fpm (flash per minute)
Horizontal coverage	360°
Input voltage	110 – 230 Vac
Average power consumption	55 W day mode @20fpm, τ = 500 ms
Peak power consumption	250 W day mode / 35 W night mode
Average life	100 000 hours
Temperature range	from -40 °C to +55 °C
Protection degree	IP66
Material of the body	Anodized aluminum
Material of the transparent cap	Polycarbonate
Connection	M/F connector IP68 for cable up to ø 13 mm
Weight	11 Kg + 13 Kg (Junction Box)
Radiation shield	Stainless steel AISI 304
Optional fixing SCSG_HDGS	Mounting hardware for "L" shaped sections (50x50 mm min.; 160x160 mm max.); circular profiles (min. ø = 48,3 mm; max. ø 219,1 mm). Adjustable fixing plate (± 60° on the horizontal plan).
Optional codes	MIOLAC-M1_23SC Equipped with Faraday cage, SEGS23P20K_C2K_15_FC compliant MIOLAC-M1_23SL Powerline control (dedicated control board needed), SEGS23P20K_C2K_17 compliant

TECHNICAL DRAWINGS

