



PHOTOMETRIC STANDARD COMPLIANCE



ICAO ANNEX 14, VOLUME I  
**TYPE B** - LOW INTENSITY OBSTACLE LIGHT;  
 CAP 168 – LOW INTENSITY GROUP A.



FAA AC 150/5345-43F;  
**TYPE L-810.**

KEY FEATURES

- designed and manufactured in Italy by Clampco Sistemi
- resistance to corrosion
- easy way for mounting – plug 'n' play connection
- the lowest weight in the market

\* optional FARADAY CAGE

SPECIFICATIONS

Order Code	SEGD12A32_1	SEGD24A32_1	SEGD48A32_1	SEGD23A32_1
Typical use	Night time			
Light source	LED			
Type of beacon	Double (main + stand-by) Steady			
Colour	Red according to CIE Chromaticity Boundary			
Light Intensity	>32.5 cd			
Horizontal coverage	360°			
Input voltage	12 Vdc	24 Vdc	48 Vdc	110 – 230 Vac
Power consumption	5 W	5 W	5 W	5 W
Average life	100 000 hours			
Temperature range	from -40 °C to +55 °C			
Protection degree	IP66			
Material of the body	Glass Reinforced Plastic red body (UL94-HB)			
Material of the transparent cap	Polycarbonate (UL94-V2)			
Connection	M/F connector IP68 for cable up to ø 9-6 mm			
Weight	3 Kg			
Fixing	Stainless steel anchor basement for poles with diameter up to 82 mm.			
Special Fixing SCSG_HDGS	Mounting hardware for "L" shaped sections (50x50 mm min.; 160x160 mm max.); circular profiles (min. ø = 48,3 mm; max. ø 219.1 mm). Adjustable fixing plate (± 60° on the horizontal plan).			

TECHNICAL DRAWINGS

