



PHOTOMETRIC STANDARD COMPLIANCE



FAA AC 150/5345-43J  
**TYPE L-810 (F)** – FLASHING RED  
 OBSTRUCTION LIGHT

KEY FEATURES & BENEFITS

- designed and manufactured in Italy by Clampco Sistemi
- resistance to corrosion
- easy way for mounting – plug 'n' play connection
- patented technology
- extended power supply range: 10 to 60 Vdc, 110-230Vac
- 30 flash per minute (FFM) flashing light

SPECIFICATIONS

	LIOLB-P1_22SF	LIOLB-P1_23SF
Order Code	LIOLB-P1_22SF	LIOLB-P1_23SF
Typical use		Night time
Light source		LED
Type of beacon		Flashing
Colour	Red according to CIE Chromaticity Boundary	
Light Intensity	>32.5 cd	
Horizontal coverage	360°	
Input voltage	10 ÷ 60 Vdc	110 ÷ 230 Vac
Power consumption	3 W(peak) – 0,8 W(mean @30FPM)	4.5 W(peak) – 1 W(mean @30FPM)
Average life	100 000 hours	
Temperature range	-40 to +55 °C<	-30 to +55 °C
Protection degree	IP66	
Material of the body	Glass Reinforced Plastic red body (UL94-HB)	
Material of the transparent cap	Polycarbonate (UL94-V2)	
Connection	M/F connector IP66/68 for cable up to ø 7 - 13 mm	
Weight	700 g	
Fixing	Stainless steel anchor basement for poles with diameter up to 82 mm.	
Optional fixing SCSG_HDGS	Mounting hardware for "L" shaped sections (50x50 mm min.; 160x160 mm max.); circular profiles (min. ø = 48,3 mm; max. ø 219,1 mm). Adjustable fixing plate (± 60° on the horizontal plan)	

TECHNICAL DRAWINGS

